



**Certificate
Of
Analysis**

**Product #
10-200
Acrylic End
Sealers**

**100% Acrylic Waterproofing
Latex End-sealers**

PFI 10-200 Series 100% Acrylic Waterproofing Latex End-sealers provide superior water resistance and excellent coverage at an economical price. End-sealers in the 10-200 Series are environmentally friendly, low VOC water-based products with outstanding adhesion to many different substrates, including steel. Use of 10-200 Series End Seals results in long lasting moisture protection.

PHYSICAL CHARACTERISTICS

Weight per gallon:	8.33-9.50
% Solids by Weight:	30-45%
%Solids by Volume:	25-35%
PH:	8.0-9.0
Viscosity - Krebs	50-75 KU
Flash Point (closed cup):	N/A
Spread Rate:	300-500 sq. ft. @ 1 mil
Material VOC:	< than .80 lb / gal
Coatings VOC (-water):	<1.5 lb /gal
Delta E:	.5

Application Specifications

Method: Product can be applied by airless or assisted-airless spray.
Reduction: Water.

Special Notes

Please read the MSDS before using this product.

Effect of freezing:

Shelf life: Six months - Please rotate stock on a regular basis.

Regulatory status: This product is not considered a hazardous waste under current RCRA regulations. This product does not contain, nor is it manufactured using ozone depleting substances as listed under Section 611 of the Clean Air Act.

PremierFinishes.net