

Certificate of Analysis

Product #

10-439

Premier Finishes, Inc.

Enviro-Tech Low VOC Gloss White DTM

Enviro-Tech 10-400 series enamels and primers represent a new generation of environmentally friendly, high-performing water-base finishes for ferrous and non-ferrous metal surfaces. These fast drying, low VOC enamels and primers provide superior adhesion, long-term durability and excellent water and corrosion resistance when applied to most metal surfaces including steel, galvanized, brass, zinc, iron, and even aluminum. Easy water clean-up and a total VOC under 1 lb. per gallon, these super tough easy-to-use finishes meet even the most stringent US and state VOC laws for volatile organic compounds. **10-400 Series Enviro-Tech** enamels can be tinted in a wide variety of pastel and mid-tone colors and available in a satin-semi-gloss sheen. Special sheen requests are available.

PHYSICAL CHARACTERISTICS

 Weight per gallon:
 9.99

 % Solids by weight:
 46.04

 % Solids by volume:
 34.33

 PH:
 8.5 – 9.5

 Viscosity - Krebs:
 100 – 105KU

Flash Point (closed cup): >200F

Spread Rate: 551 sq. ft. @ 1 mil Material VOC: 0.46 lb. / gal. Coatings VOC (-water): 1.21 lb. / gal.

Gloss: 80+

Application Specifications

Surface: Must be clean and free of all contamination such as oil, rust, dirt, and particulate matter. Surface Iron Phosphate pretreatment and 10-400 Primer is recommended for best adhesion and performance.

Method: Mix thoroughly before and during use. Applied wet film thickness: 3-4 mils. Applied dry film thickness: 1.0-1.5. **Reduction:** Water if necessary, up to 5%. Do not apply at temperatures below 50F. Application temperature < 120F. Excessive film thickness will retard dry times and create at recoat window issue. Poor air movement in drying areas will increase dry time. Painted parts should be allowed at least 24 hours before being placed outdoors. **Clean-up:** Warm soapy water.

Special Notes

Please read the SDS before using this product. Shelf life: Six months – please rotate stock on a regular basis. Do not freeze, Product will not recover.

PremierFinishes.net