



Certificate  
of  
Analysis

Product #

10-500

Premier Finishes, Inc.

## TuffKote Super Prime 100% Acrylic Exterior Latex – Bright White

### PHYSICAL CHARACTERISTICS

|                           |                     |
|---------------------------|---------------------|
| Weight per gallon:        | 10.71               |
| % Solids by weight:       | 60.08               |
| % Solids by volume:       | 44.65               |
| PH:                       | 8.5 – 9.5           |
| Viscosity – Brook:        | 85-90KU             |
| Flash Point (closed cup): | None                |
| Gloss@ 60deg:             | NA                  |
| Spread Rate:              | 716 sq. ft. @ 1 mil |
| Material VOC:             | 0.80 lb. / gal.     |
| Coatings VOC (-water):    | 0.32 lb. / gal.     |
| Delta E:                  | .5                  |

### Application Specifications

**Method:** Product can be applied by brush, airless or assisted-airless spray.

**Reduction:** Water, if necessary.

### Special Notes

**Please read the SDS before using this product.**

**Shelf life:** Six months – please rotate stock on a regular basis. Do not freeze. Product will not recover.

**Regulatory status:** This product is not considered a hazardous waste under current RCRA regulations. This product does not contain, nor is it manufactured using ozone depleting substances as listed under Section 611 of the Clean Air Act.

PremierFinishes.net