



**Certificate  
of Analysis**

**Product #**

**10-557**

**Premier Finishes, Inc.**

**White Acrylic FJ Pine Primer**

**PHYSICAL CHARACTERISTICS**

<b>Weight per gallon:</b>	<b>12.99</b>
<b>% Solids by weight:</b>	<b>66.31</b>
<b>% Solids by volume:</b>	<b>46.48</b>
<b>PH:</b>	<b>8.3 – 9.3</b>
<b>Viscosity - #3 ZAHN:</b>	<b>12" – 14"</b>
<b>Flash Point (closed cup):</b>	<b>None</b>
<b>Spread Rate:</b>	<b>746 sq. ft. @ 1 mil</b>
<b>Material VOC:</b>	<b>0.14 lb. / gal. @ 0</b>
<b>Coatings VOC (-water):</b>	<b>0.27 lb. / gal. @ 0</b>
<b>Delta E:</b>	<b>.5</b>

**Application Specifications**

**Method:** Product can be applied by airless or assisted-airless spray or vacuum coater.

**Reduction:** None

**Special Notes**

**Please read the SDS before using this product.**

**Shelf life:** Six months – please rotate stock on a regular basis. Do not freeze. Product will not recover.

**Regulatory status:** This product is not considered a hazardous waste under current RCRA regulations. This product does not contain, nor is it manufactured using ozone depleting substances as listed under Section 611 of the Clean Air Act.

**PremierFinishes.net**