



## 11-200 SERIES

### Premier Finishes, Inc. **SOLAR SHIELD Semi Transparent Woodland Series**

**Premier Finishes 11-200 Solar Shield Woodland Series** Urethane Acrylic Stains provide exceptional durability and long-lasting protection for exterior Lap Siding, Cement Board, and engineered wood substrates. Superior long-lasting beauty and rustic look on modular homes, cabins, and backyard structures. **Premier Finishes 11-200 Solar Shield Woodland Series** stains provide unsurpassed UV and moisture protection. Supplied in Semi- Gloss, Satin, and Matte finish.

**Application** – Use at temperatures above 50 degrees F. Apply with airless sprayer, brush, or roller. Product is bucket ready – no reduction necessary. Brush off dust or dirt prior to application.

**Health & Safety** – Use with adequate ventilation. Approved respirator will reduce irritation. Wear safety goggles during application. If eye contact occurs, flush with water and consult a physician.

**Dry Time** – 20-30 minutes average, depending on air temperature and relative humidity.

**Clean Up** – Soap and Water. Use suitable absorbent material on spills and dispose of waste in accordance with local, state, and federal regulations.

**Storage** - Optimum storage and handling temperature for **Premier Finishes 11-200 Solar Shield** Woodland Series is 40-100 F (4-38 C) in a dry area protected from direct sunlight. Protect from freezing, product will not recover.

#### Advantages

- Deep Penetrating Natural Oils combined in a water-borne delivery
- Maintains Appearance for up to 10 Years
- Durable & Flexible Waterborne Alkyd-Urethane technology
- Excellent Scuff & Abrasion Resistance
- High Performance Polycarbonate Urethane
- Excellent Adhesion & Flexibility
- Superior Resistance to Fading, Cracking, and Peeling
- Self Cross Linked for Unmatched Moisture Protection
- Accepts Most Paints for Easy Future Refinishing
- Mildew Resistant & Easy to Clean
- Easy to Apply & recoat-able
- Environmentally Friendly-Low VOC

Material Safety Data Sheets are available upon request or visit [PremierFinishes.net](http://PremierFinishes.net)

#### Physical Properties

<b>Weight per gallon:</b>	<b>8.87 +/- .50</b>	<b>Spread Rate:</b>	<b>200-300 sq. ft. per gal.</b>
<b>% Solids by weight:</b>	<b>34.02</b>	<b>Material VOC:</b>	<b>1.10 lb. / gal.</b>
<b>% Solids by volume:</b>	<b>31.30</b>	<b>Coatings VOC (-water):</b>	<b>0.43 lb. / gal.</b>
<b>PH:</b>	<b>8.5 – 9.5</b>	<b>Viscosity - Krebs:</b>	<b>100-105KU</b>

**PremierFinishes.net**

**Flash Point (closed cup):**        **None**