



# SUPER-PREP

## Multi-Surface Prep-coat & Primer

**Super-Prep** is fast drying, hi-hide multi-surface coating used to seal and prime drywall, joints, and paper ensuring a uniform porosity and sheen for latex based finish coats.

- Durable, clean, white finish
- Outstanding hold-out when used as a under-coat for texture or smooth-wall finishes.
- Seals and primes surfaces that most prep-coats are not designed to coat.
- Versatile and environmentally friendly
- Economical coating that provides the professional painter with one hi-hide product that does it all.



### PREMIER FINISHES

PO Box 3146, Oregon City, OR 97045  
503-241-2770 | [office@premierfinishes.net](mailto:office@premierfinishes.net) |  
[PremierFinishes.net](http://PremierFinishes.net)

# SUPER-PREP

## Multi-Surface Prep-coat & Primer



**Application:** Use at temperatures above 50 degrees F. Apply with airless sprayer, brush or roller. Product is bucket ready –no reduction necessary. Brush off dust or dirt on wall. Apply as you would any primer.

### Physical Characteristics

<b>%Solids by Vol.:</b>	24.28
<b>%Solids by Wgt.:</b>	38.02
<b>pH:</b>	8.5-9.5
<b>Visc. Krebs:</b>	90KU
<b>Spread Rate:</b>	389 sq. ft. @ 1 mil
<b>VOC:</b>	0.07 lb./gal.
<b>VOC (-water):</b>	0.29 lb./gal.
<b>Flash Point:</b>	None (closed cup)
<b>Delta E:</b>	0.5



Read product label for safety and cautions prior to using this product. A Safety Data Sheet is available at [PremierFinishes.net](http://PremierFinishes.net).

Not considered a hazardous waste under current RCRA regulations. Does not contain, nor is it manufactured using ozone depleting substances as listed under Section 611 of the Clean Air Act.



### PREMIER FINISHES

PO Box 3146, Oregon City, OR 97045  
503-241-2770 | [office@premierfinishes.net](mailto:office@premierfinishes.net) |  
[PremierFinishes.net](http://PremierFinishes.net)